



Family

Rundo

Circular luminaires with an aluminium profile come in two heights, 62 mm and 87 mm. Rundo luminaires feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Rundo luminaires with a diameter of up to 1150 mm can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.



Type of installation	Surface, Wall mounted, Suspended
Light distribution	Direct, Direct-indirect
Colour of the luminaires	Black, Silver, White
Colour Temperature	3000 K warm white, 4000 K cool white, 2700 K - 6500 K Tunable White
Material	Aluminium
Light source	LED MODUL
LED type	Tunable White
MacAdam Light source	3
Connection of the luminaires	ON/OFF DALI ON/OFF + 1h emergency Other type of dimming ON/OFF + 3h emergency DALI DT8 DALI + bluetooth ON/OFF multiwatt
Lifetime	L80/B20, L80/B10, L90/B50 50 000 hours
Warranty	60 months

Luminaire family variants Rundo





Rundo



Assembly



Light distribution




Energy class

energy_class_g

Marks


Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
290-241K-10GEE/840, W	ø 410 × 24	10	1450	4000	< 17.5
290-240K-10GEE/840, W	ø 410 × 24	11.3	1540	4000	< 21.7
290-240K-10GGE/840, W	ø 410 × 24	18.6	2550	4000	< 23.4
290-241K-10GGE/840, W	ø 410 × 24	20.8	3000	4000	< 20
290-240K-10GHE/840, W	ø 410 × 24	29.7	4060	4000	< 25.1
290-241K-10GHE/840, W	ø 410 × 24	35.2	5040	4000	< 21.8
290-260K-10GEE/840, W	ø 630 × 24	14.9	2090	4000	< 19.6
290-261K-10GEE/840, W	ø 630 × 24	17	2550	4000	< 17.6
290-260K-10GGE/840, W	ø 630 × 24	21.6	3060	4000	< 20.9
290-261K-10GGE/840, W	ø 630 × 24	24	3600	4000	< 18.8
290-260K-10GHE/840, W	ø 630 × 24	29.2	4100	4000	< 21.9
290-261K-10GHE/840, W	ø 630 × 24	33.9	4990	4000	< 20
290-260K-10GIE/840, W	ø 630 × 24	40.8	5630	4000	< 23
290-261K-10GIE/840, W	ø 630 × 24	51.6	7420	4000	< 21.4

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF DALI ON/OFF + 3h emergency
	Ra	80

For pendant assembly, you must order a pendant set containing cables and a ceiling cup.

Rundo



Assembly



Light distribution




Energy class

energy_class_g

Marks

Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
290-241K-10GEE/840, W + 00-00334, W	ø 410 × 24	10	1450	4000	< 17.5
290-240K-10GEE/840, W + 00-00334, W	ø 410 × 24	11.3	1540	4000	< 21.7
290-240K-10GGE/840, W + 00-00334, W	ø 410 × 24	18.6	2550	4000	< 23.4
290-241K-10GGE/840, W + 00-00334, W	ø 410 × 24	20.8	3000	4000	< 20
290-240K-10GHE/840, W + 00-00334, W	ø 410 × 24	29.7	4060	4000	< 25.1
290-241K-10GHE/840, W + 00-00334, W	ø 410 × 24	35.2	5040	4000	< 21.8
290-260K-10GEE/840, W + 00-00334, W	ø 630 × 24	14.9	2090	4000	< 19.6
290-261K-10GEE/840, W + 00-00334, W	ø 630 × 24	17	2550	4000	< 17.6
290-260K-10GGE/840, W + 00-00334, W	ø 630 × 24	21.6	3060	4000	< 20.9
290-261K-10GGE/840, W + 00-00334, W	ø 630 × 24	24	3600	4000	< 18.8
290-260K-10GHE/840, W + 00-00334, W	ø 630 × 24	29.2	4100	4000	< 21.9
290-261K-10GHE/840, W + 00-00334, W	ø 630 × 24	33.9	4990	4000	< 20
290-260K-10GIE/840, W + 00-00334, W	ø 630 × 24	40.8	5630	4000	< 23
290-261K-10GIE/840, W + 00-00334, W	ø 630 × 24	51.6	7420	4000	< 21.4

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF DALI ON/OFF + 3h emergency
	Ra	80


For pendant assembly, you must order a pendant set containing cables and a ceiling cup.

Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
290-241K-10GEE/840, W + 00-00384-1000/RUN, ø 410 × 24 W		10	1450	4000	< 17.5
290-240K-10GEE/840, W + 00-00384-1000/RUN, ø 410 × 24 W		11.3	1540	4000	< 21.7
290-240K-10GGE/840, W + 00-00384-1000/RUN, ø 410 × 24 W		18.6	2550	4000	< 23.4
290-241K-10GGE/840, W + 00-00384-1000/RUN, ø 410 × 24 W		20.8	3000	4000	< 20
290-240K-10GHE/840, W + 00-00384-1000/RUN, ø 410 × 24 W		29.7	4060	4000	< 25.1
290-241K-10GHE/840, W + 00-00384-1000/RUN, ø 410 × 24 W		35.2	5040	4000	< 21.8
290-260K-10GEE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		14.9	2090	4000	< 19.6
290-261K-10GEE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		17	2550	4000	< 17.6
290-260K-10GGE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		21.6	3060	4000	< 20.9
290-261K-10GGE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		24	3600	4000	< 18.8
290-260K-10GHE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		29.2	4100	4000	< 21.9
290-261K-10GHE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		33.9	4990	4000	< 20
290-260K-10GIE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		40.8	5630	4000	< 23
290-261K-10GIE/840, W + 00-00384-1000/RUN, ø 630 × 24 W		51.6	7420	4000	< 21.4

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

Notes	Colour of the luminaires	<div> <div></div> <div></div> <div></div> </div>
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF DALI ON/OFF + 3h emergency
	Ra	80
	For pendant assembly, you must order a pendant set containing cables and a ceiling cup.	

Rundo



Assembly



Light distribution




Energy class

energy_class_g


Marks



Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
190-241K-10GGEI/840, W	ø 400 × 62	27.4	3500	4000	< 21.6
190-240K-10GGEI/840, W	ø 400 × 62	29.1	3500	4000	< 24
190-251K-10GGEI/840, W	ø 500 × 62	35.3	4500	4000	< 20.9
190-250K-10GGEI/840, W	ø 500 × 62	36.4	4500	4000	< 23.3
190-251I-10GGEI/840, W	ø 500 × 62	44.5	4500	4000	< 16.6
190-250I-10GGEI/840, W	ø 500 × 62	48.4	4500	4000	< 19.4
190-261K-10GGEI/840, W	ø 600 × 62	39.9	5500	4000	< 21
190-260K-10GGEI/840, W	ø 600 × 62	40.4	5500	4000	< 22.7
190-2A0K-10GEE/840, W	ø 1150 × 87	94.9	13020	4000	< 20.8
190-2A1K-10GEE/840, W	ø 1150 × 87	106	14390	4000	< 19.9
190-2A0K-10GGE/840, W	ø 1150 × 87	127.5	17270	4000	< 22
190-2A1K-10GGE/840, W	ø 1150 × 87	143.2	19290	4000	< 20.9
190-2A0K-10GHE/840, W	ø 1150 × 87	145.3	19480	4000	< 22.5
190-2A1K-10GHE/840, W	ø 1150 × 87	179.8	23900	4000	< 21.7

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white 2700 K - 6500 K Tunable White
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF DALI ON/OFF + 1h emergency Other type of dimming ON/OFF + 3h emergency DALI DT8 DALI + bluetooth ON/OFF multiwatt
	Ra	80 90
	For pendant assembly, you must order a pendant set containing cables and a ceiling cup.	


Rundo




Assembly	Light distribution
	
Energy class	Marks
energy_class_g	

Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
190-241K-10GGEI/840, W + 00-00334, W	ø 400 × 62	27.4	3500	4000	< 21.6
190-240K-10GGEI/840, W + 00-00334, W	ø 400 × 62	29.1	3500	4000	< 24
190-261K-10GGEI/840, W + 00-00334, W	ø 600 × 62	39.9	5500	4000	< 21
190-260K-10GGEI/840, W + 00-00334, W	ø 600 × 62	40.4	5500	4000	< 22.7
190-2A0K-10GEE/840, W + 00-00374, W	ø 1150 × 87	94.9	13020	4000	< 20.8
190-2A1K-10GEE/840, W + 00-00374, W	ø 1150 × 87	106	14390	4000	< 19.9
190-2A0K-10GGE/840, W + 00-00374, W	ø 1150 × 87	127.5	17270	4000	< 22
190-2A1K-10GGE/840, W + 00-00374, W	ø 1150 × 87	143.2	19290	4000	< 20.9
190-2A0K-10GHE/840, W + 00-00374, W	ø 1150 × 87	145.3	19480	4000	< 22.5
190-2A1K-10GHE/840, W + 00-00374, W	ø 1150 × 87	179.8	23900	4000	< 21.7

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF DALI ON/OFF + 1h emergency ON/OFF + 3h emergency ON/OFF multiwatt
	Ra	80
	Luminaires come complete with all necessary accessories.	

Rundo



Assembly



Light distribution




Energy class

energy_class_g

Marks

Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
190-241K-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 400 × 62 W		27.4	3500	4000	< 21.6
190-240K-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 400 × 62 W		29.1	3500	4000	< 24
190-241I-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 400 × 62 W		32.8	3500	4000	< 16.7
190-240I-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 400 × 62 W		37.8	3500	4000	< 20.1
190-251K-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 500 × 62 W		35.3	4500	4000	< 20.9
190-250K-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 500 × 62 W		36.4	4500	4000	< 23.3
190-251I-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 500 × 62 W		44.5	4500	4000	< 16.6
190-250I-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 500 × 62 W		48.4	4500	4000	< 19.4
190-261K-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 600 × 62 W		39.9	5500	4000	< 21
190-260K-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 600 × 62 W		40.4	5500	4000	< 22.7
190-261I-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 600 × 62 W		51.4	5500	4000	< 17.1
190-260I-10GGEI/840, W + 00-00384-1000/RUN, \varnothing 600 × 62 W		54.7	5500	4000	< 18.8
190-2A0K-10GEE/840, W + 00-00384-1000/RUN, \varnothing 1150 × 87 W		94.9	13020	4000	< 20.8
190-2A1K-10GEE/840, W + 00-00384-1000/RUN, \varnothing 1150 × 87 W		106	14390	4000	< 19.9
190-2A0K-10GGE/840, W + 00-00384-1000/RUN, \varnothing 1150 × 87 W		127.5	17270	4000	< 22
190-2A1K-10GGE/840, W + 00-00384-1000/RUN, \varnothing 1150 × 87 W		143.2	19290	4000	< 20.9
190-2A0K-10GHE/840, W + 00-00384-1000/RUN, \varnothing 1150 × 87 W		145.3	19480	4000	< 22.5
190-2A1K-10GHE/840, W + 00-00384-1000/RUN, \varnothing 1150 × 87 W		179.8	23900	4000	< 21.7

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF DALI ON/OFF + 1h emergency ON/OFF + 3h emergency ON/OFF multiwatt
	Ra	80
	Luminaires come complete with all necessary accessories.	

Legend

Type of installation

	Recessed lights		Wall mounted lights
	Semi-recessed luminaire		Suspended lights
	Surface lights		Free-standing lights
	3 circuit track lights		Table lamp lights

Light distribution

	Direct luminaire
	Direct-indirect luminaire
	Indirect luminaire

Light source

	Tunable White adjusting the color temperature		RealWhite true display of white color
	RealColour true display of colors Ra≥97		StrongColour highlight one color

Marks

	Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
	European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
	Luminaires are certified according to the European ENEC system
	Recommended mounting hole size

IPxy IP code indicating the degree of protection of live parts

EAC Eurasian Conformity

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

Optic system

Electrical connection

Colour

Optic system

B	Microprismatic system, low UGR	L	Plain aluminium reflector
C	Clear cover	M	Matt parabolic louvre
D	Asymmetric reflector	S	SPOT - narrow angle
E	Polished parabolic louvre, high LOR	U	MEDIUM - middle angle
F	FLOOD - wide angle	W	Wide beam angle
I	Microprismatic optical system	Z	Plastic louver, low UGR
K	Opal diffuser		

Electrical connection

/BT	Luminaires controlled via Bluetooth technology	P	Sensor and electronic ballast
D	DALI dimmable	T	By switch dimmable (touch dimm)
E	Electronic ballast non-dimmable	TD	DALI or by switch (touch dimm) dimmable
M	Electronic ballast non-dimmable with 1h emergency	U	Dimmable luminaire with dimmer on the luminaire
M3	Electronic ballast non-dimmable with 3h emergency		

Colour

W	 RAL 9003	B	 RAL 9005	S	 TIGER 09/90530
1021	 RAL 1021	2000	 RAL 2000	3020	 RAL 3020
5015	 RAL 5015	6018	 RAL 6018	7016	 RAL 7016
9006	 RAL 9006	9010	 RAL 9010		

Značky typu

	Smart – Luminaire or the lighting system controlled by motion, daylight or via smart devices using Bluetooth technology
	Acoustic – Luminaire with acoustic absorption properties which reduce disturbing noise and improve the acoustics of the room
	Multiwatt – Luminaires with individually adjustable luminous flux using a special antenna or mobile application

UGR UGR – The luminaire suitable for office spaces