



Luminaire

Ilbi


108-301K-20GEE/830, S



When Matúš Opálka closed himself into his study for a month, we were wondering what he would come up with. He designed lighting that gives off a gentle but luxurious effect. The indirect two-sided emission with reflection from the wall creates a pleasantly soft light with adjustable intensity.


Design Matúš Opálka

Technical drawing



Type of installation	Surface, Wall mounted, Suspended
Light distribution	Indirect
Luminaire shape	Angular
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	60 months
Description of luminaires	Luminaire surface/wall mounted/suspended
item description	independent luminaire
Dimensions	616 mm × 37 mm × 106 mm
Weight	2 kg
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux	2040 lm ± 10 %
Colour Temperature	3000 K warm white
Luminous efficacy test	99 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, $\rho=70,50,20$	30

Curve



Luminaire power input 20.7 W \pm 10 %

Connection of the luminaires Electronic ballast non-dimmable

Electrical voltage 220-240V

Frequency 50-60Hz

⊕ CE IP 20

Downloads

Installation instructions



Photos



Accessories**00-00350, K**
cable 3x0,75 1000mm**00-00351, K**
cable 4x0,75 1000mm**00-00352, K**
cable 3x0,75 2000mm**00-00353, K**
cable 4x0,75 2000mm**00-00354, K**
cable 5x0,75 1000mm**00-00355, K**
cable 5x0,75 2000mm**00-00370, S**
ceiling cup 80x80x32mm**01-0007, N**
wire suspension
2000mm**108-0002, F**
wall fastening for
108-301K