



Luminaire

Gatu

21-001F-20GDE/840, S



By combining a simple design and adding functionality, we achieved the Gatu family lighting system. You can turn the built-in luminaire with a tiltable reflector toward the desired object as required. In addition to highly illuminating LEDs with a color rendering of $R_a > 80$ or $R_a > 90$, the lighting also contains a wide range of light sources.

Technical drawing



Type of installation	Recessed
Light distribution	Direct
Luminaire shape	Angular
Colour of the luminaires	Silver
Material	Sheet metal
Lifetime	L80/B10 50 000 hours
Warranty	60 months
Description of luminaires	Luminaire recessed
Dimensions	350 mm × 185 mm × 95 mm
Weight	1.7 kg
Light source	LED MODUL
Type of optical system	Reflector
Luminous flux	1280 lm ± 10 %
Colour Temperature	4000 K cool white
Luminous efficacy test	132 lm/W
MacAdam Light source	3
Colour rendering index	80
Beam angle	41°
UGR max. X=4H Y=8H, $\rho=70,50,20$	15.3

Curve



Luminaire power input 9.7 W \pm 10 %

Connection of the luminaires Electronic ballast non-dimmable

Electrical voltage 220-240V

Frequency 50-60Hz

   IP 20

Realization



Downloads

Installation instructions



Photos

