


**Family**

# Lipo35

Type of installation	Surface, Suspended
Light distribution	Direct
Colour of the luminaires	Black, Silver, White
Colour Temperature	3000 K warm white, 4000 K cool white
Material	Aluminium
Light source	LED MODUL
MacAdam Light source	2
Connection of the luminaires	ON/OFF DALI
Lifetime	L90/B50 50 000 hours
Warranty	60 months

**Luminaire family variants Lipo35**


**Lipo35**
**Assembly**


**Light distribution**

**Energy class**

A++, A+, A

**Marks**


Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
35-550K-10GEE/840, W	561 × 37 × 75	7.7	970	4000	-
35-550K-10GGE/840, W	561 × 37 × 75	11	1330	4000	-
35-550K-15GEE/840, W	842 × 37 × 75	11.6	1460	4000	-
35-550K-15GGE/840, W	842 × 37 × 75	16.5	2000	4000	-
35-550K-20GEE/840, W	1122 × 37 × 75	15.5	1950	4000	-
35-550K-20GGE/840, W	1122 × 37 × 75	22	2670	4000	-
35-550K-25GEE/840, W	1403 × 37 × 75	19.3	2440	4000	-
35-550K-25GGE/840, W	1403 × 37 × 75	27.6	3340	4000	-
35-550K-30GEE/840, W	1683 × 37 × 75	23.2	2930	4000	-
35-550K-30GGE/840, W	1683 × 37 × 75	33.1	4010	4000	-
35-550K-35GEE/840, W	1964 × 37 × 75	27	3420	4000	-
35-550K-35GGE/840, W	1964 × 37 × 75	38.6	4670	4000	-
35-550K-40GEE/840, W	2244 × 37 × 75	30.9	3900	4000	-
35-550K-40GGE/840, W	2244 × 37 × 75	44.1	5340	4000	-
35-550K-50GEE/840, W	2805 × 37 × 75	38.6	4880	4000	-
35-550K-50GGE/840, W	2805 × 37 × 75	55.1	6680	4000	-
35-550K-60GEE/840, W	3366 × 37 × 75	46.4	5860	4000	-
35-550K-60GGE/840, W	3366 × 37 × 75	66.1	8020	4000	-
35-550K-80GEE/840, W	4488 × 37 × 75	61.8	7810	4000	-
35-550K-80GGE/840, W	4488 × 37 × 75	88.2	10690	4000	-

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Opal diffuser
	Connection of the luminaires	ON/OFF DALI
	Ra	80

## Lipo35

### Assembly



### Light distribution




### Energy class

A++, A+, A

### Marks



Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
35-500K-10GEE/840, W	561 × 37 × 60	7.7	720	4000	-
35-500K-10GGE/840, W	561 × 37 × 60	11	990	4000	-
35-500K-15GEE/840, W	842 × 37 × 60	11.6	1090	4000	-
35-500K-15GGE/840, W	842 × 37 × 60	16.5	1490	4000	-
35-500K-20GEE/840, W	1122 × 37 × 60	15.5	1450	4000	-
35-500K-20GGE/840, W	1122 × 37 × 60	22	1990	4000	-
35-500K-25GEE/840, W	1403 × 37 × 60	19.3	1820	4000	-
35-500K-25GGE/840, W	1403 × 37 × 60	27.6	2490	4000	-
35-500K-30GEE/840, W	1683 × 37 × 60	23.2	2180	4000	-
35-500K-30GGE/840, W	1683 × 37 × 60	33.1	2990	4000	-
35-500K-35GEE/840, W	1964 × 37 × 60	27	2550	4000	-
35-500K-35GGE/840, W	1964 × 37 × 60	38.6	3490	4000	-
35-500K-40GEE/840, W	2244 × 37 × 60	30.9	2910	4000	-
35-500K-40GGE/840, W	2244 × 37 × 60	44.1	3980	4000	-
35-500K-50GEE/840, W	2805 × 37 × 60	38.6	3640	4000	-
35-500K-50GGE/840, W	2805 × 37 × 60	55.1	4980	4000	-
35-500K-60GEE/840, W	3366 × 37 × 60	46.4	4370	4000	-
35-500K-60GGE/840, W	3366 × 37 × 60	66.1	5980	4000	-
35-500K-80GEE/840, W	4488 × 37 × 60	61.8	5820	4000	-
35-500K-80GGE/840, W	4488 × 37 × 60	88.2	7970	4000	-

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Opal diffuser
	Connection of the luminaires	ON/OFF DALI
	Ra	80

**Lipo35**
**Assembly**


**Light distribution**

**Energy class**

A++, A+, A

**Marks**


Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
35-250K-10GEE/840, W	561 × 37 × 75	7.7	970	4000	-
35-250K-10GGE/840, W	561 × 37 × 75	11	1330	4000	-
35-250K-15GEE/840, W	842 × 37 × 75	11.6	1460	4000	-
35-250K-15GGE/840, W	842 × 37 × 75	16.5	2000	4000	-
35-250K-20GEE/840, W	1122 × 37 × 75	15.5	1950	4000	-
35-250K-20GGE/840, W	1122 × 37 × 75	22	2670	4000	-
35-250K-25GEE/840, W	1403 × 37 × 75	19.3	2440	4000	-
35-250K-25GGE/840, W	1403 × 37 × 75	27.6	3340	4000	-
35-250K-30GEE/840, W	1683 × 37 × 75	23.2	2930	4000	-
35-250K-30GGE/840, W	1683 × 37 × 75	33.1	4010	4000	-
35-250K-35GEE/840, W	1964 × 37 × 75	27	3420	4000	-
35-250K-35GGE/840, W	1964 × 37 × 75	38.6	4670	4000	-
35-250K-40GEE/840, W	2244 × 37 × 75	30.9	3900	4000	-
35-250K-40GGE/840, W	2244 × 37 × 75	44.1	5340	4000	-
35-250K-50GEE/840, W	2805 × 37 × 75	38.6	4880	4000	-
35-250K-50GGE/840, W	2805 × 37 × 75	55.1	6680	4000	-
35-250K-60GEE/840, W	3366 × 37 × 75	46.4	5860	4000	-
35-250K-60GGE/840, W	3366 × 37 × 75	66.1	8020	4000	-
35-250K-80GEE/840, W	4488 × 37 × 75	61.8	7810	4000	-
35-250K-80GGE/840, W	4488 × 37 × 75	88.2	10690	4000	-

Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Opal diffuser
	Connection of the luminaires	ON/OFF DALI
	Ra	80

## Lipo35

### Assembly



### Light distribution



### Energy class


A++, A+, A

### Marks



Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
35-200K-10GEE/840, W	561 × 37 × 60	7.7	720	4000	-
35-200K-10GGE/840, W	561 × 37 × 60	11	990	4000	-
35-200K-15GEE/840, W	842 × 37 × 60	11.6	1090	4000	-
35-200K-15GGE/840, W	842 × 37 × 60	16.5	1490	4000	-
35-200K-20GEE/840, W	1122 × 37 × 60	15.5	1450	4000	-
35-200K-20GGE/840, W	1122 × 37 × 60	22	1990	4000	-
35-200K-25GEE/840, W	1403 × 37 × 60	19.3	1820	4000	-
35-200K-25GGE/840, W	1403 × 37 × 60	27.6	2490	4000	-
35-200K-30GEE/840, W	1683 × 37 × 60	23.2	2180	4000	-
35-200K-30GGE/840, W	1683 × 37 × 60	33.1	2990	4000	-
35-200K-35GEE/840, W	1964 × 37 × 60	27	2550	4000	-
35-200K-35GGE/840, W	1964 × 37 × 60	38.6	3490	4000	-
35-200K-40GEE/840, W	2244 × 37 × 60	30.9	2910	4000	-
35-200K-40GGE/840, W	2244 × 37 × 60	44.1	3980	4000	-
35-200K-50GEE/840, W	2805 × 37 × 60	38.6	3640	4000	-
35-200K-50GGE/840, W	2805 × 37 × 60	55.1	4980	4000	-
35-200K-60GEE/840, W	3366 × 37 × 60	46.4	4370	4000	-
35-200K-60GGE/840, W	3366 × 37 × 60	66.1	5980	4000	-
35-200K-80GEE/840, W	4488 × 37 × 60	61.8	5820	4000	-
35-200K-80GGE/840, W	4488 × 37 × 60	88.2	7970	4000	-

## Notes

Colour of the  
luminaires 

Colour Temperature 3000 K warm white  
4000 K cool white

Optic system Opal diffuser

Connection of the  
luminaires ON/OFF  
DALI

Ra 80

## Legend

### Type of installation

	Recessed lights		Wall mounted lights
	Semi-recessed luminaire		Suspended lights
	Surface lights		Free-standing lights
	3 circuit track lights		Table lamp lights

### Light distribution

	Direct luminaire
	Direct-indirect luminaire
	Indirect luminaire

### Light source

	Tunable White adjusting the color temperature		RealWhite true display of white color
	RealColour true display of colors Ra≥97		StrongColour highlight one color

### Marks

	Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
	European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
	Luminaires are certified according to the European ENEC system
	Recommended mounting hole size
	IP code indicating the degree of protection of live parts
	Eurasian Conformity

### 09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

Optic system

Electrical connection

Colour

### Optic system

C	Clear cover	L	Plain aluminium reflector
D	Asymmetric reflector	M	Matt parabolic louvre
E	Polished parabolic louvre, high LOR	S	SPOT - narrow angle
F	FLOOD - wide angle	U	MEDIUM - middle angle
I	Microprismatic optical system	W	Wide beam angle
K	Opal diffuser		

### Electrical connection

D	DALI dimmable	P	Sensor and electronic ballast
E	Electronic ballast non-dimmable	T	By switch dimmable (touch dimm)
M	Electronic ballast non-dimmable with 1h emergency	TD	DALI or by switch (touch dimm) dimmable
M3	Electronic ballast non-dimmable with 3h emergency	U	Dimmable luminaire with dimmer on the luminaire

### Colour

W		White	B		Black	S		Silver
1021		RAL 1021	3000		RAL 3000	6021		RAL 6021
7006		RAL 7006	7045		RAL 7045			