



Family

Moza


A simple design with maximum functionality. We introduce Moza accent LED lighting, that attracts attention with its appearance. That is why they are utilized especially in shopping centers, car showrooms and shop windows. The luminaires include a highly luminous LED with a color rendering of $Ra > 80$ or $Ra > 90$ as well as sources for illuminating objects.

Type of installation	Suspended
Light distribution	Direct
Colour of the luminaires	Black, Silver, White
Colour Temperature	3000 K warm white, 4000 K cool white, 3500 K neutral white, Meat, Bakery products, Fruit, Silver
Material	Aluminium
Light source	LED MODUL
LED type	Strong Colour, Real Colour, Real White
Connection of the luminaires	ON/OFF
Lifetime	L80/B20, L80/B10 0 hours

Luminaire family variants Moza



Moza



Assembly



Light distribution



Energy class

A++, A+, A


Marks



Notes	Beam angle	24 - 62 °
	Colour of the luminaires	● ● ●
	Colour Temperature	3000 K warm white 4000 K cool white 3500 K neutral white Meat Bakery products Fruit Silver
	Optic system	Reflector
	Connection of the luminaires	ON/OFF
	Ra	65 80 90 95 97

Luminaires come complete with all necessary accessories.

Moza



Assembly



Light distribution



Energy class

A++, A+, A

Marks











Notes	Beam angle	24 - 62 °
	Colour of the luminaires	● ● ●
	Colour Temperature	3000 K warm white 4000 K cool white 3500 K neutral white Meat Bakery products Fruit Silver
	Optic system	Reflector
	Connection of the luminaires	ON/OFF
	Ra	65 80 90 95 97




Luminaires come complete with all necessary accessories.

Legend





Type of installation

 Recessed lights	 Wall mounted lights
 Semi-recessed luminaire	 Suspended lights
 Surface lights	 Free-standing lights
 3 circuit track lights	 Table lamp lights






Light distribution

 Direct luminaire
 Direct-indirect luminaire
 Indirect luminaire

Light source

 Tunable White adjusting the color temperature	 RealWhite true display of white color
 RealColour true display of colors Ra≥97	 StrongColour highlight one color

Marks

 Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
 Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
 Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
 European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
 Luminaires are certified according to the European ENEC system

 Recommended mounting hole size

IPxy IP code indicating the degree of protection of live parts

EARC Eurasian Conformity

09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

Optic system

Electrical connection

Colour









Optic system

C Clear cover	L Plain aluminium reflector
D Asymmetric reflector	M Matt parabolic louvre
E Polished parabolic louvre, high LOR	S SPOT - narrow angle
F FLOOD - wide angle	U MEDIUM - middle angle
I Microprismatic optical system	W Wide beam angle
K Opal diffuser	

Electrical connection

D DALI dimmable	P Sensor and electronic ballast
E Electronic ballast non-dimmable	T By switch dimmable (touch dimm)
M Electronic ballast non-dimmable with 1h emergency	TD DALI or by switch (touch dimm) dimmable
M3 Electronic ballast non-dimmable with 3h emergency	U Dimmable luminaire with dimmer on the luminaire

Colour

W  White	B  Black	S  Silver
1021  RAL 1021	3000  RAL 3000	6021  RAL 6021
7006  RAL 7006	7045  RAL 7045	