



Family



Puri

We were contemplating about how to achieve total design clarity, and so the family of Puri built-in circular luminaires was built. Choose between the framed and frameless version. Mount it directly into the ceiling without cables or suspending.

| | |
|------------------------------|--|
| Type of installation | Recessed |
| Light distribution | Direct |
| Colour of the luminaires | White |
| Colour Temperature | 3000 K warm white, 4000 K cool white |
| Material | Aluminium |
| Light source | LED MODUL |
| MacAdam Light source | 3 |
| Connection of the luminaires | ON/OFF DALI ON/OFF + 1h emergency ON/OFF + 3h emergency |
| Lifetime | L80/B20, L70/B50 50 000 hours |
| Warranty | 60 months |

Luminaire family variants Puri



Puri

Assembly

Light distribution

Energy class

A++, A+, A



Marks


| Code | Dimensions l/w/h (mm) | Power of the luminaire (W) | Luminous flux (lm) | Colour Temperature (K) | UGR |
|--------------------|--------------------------|-------------------------------|-----------------------|------------------------------|--------|
| 140-043K-10GEE/840 | ø 236 × 125 | 16.7 | 900 | 4000 | < 20.9 |
| 140-052K-10GHE/840 | ø 355 × 125 | 17.1 | 1540 | 4000 | < 20.2 |
| 140-052K-10GIE/840 | ø 435 × 125 | 32.8 | 3000 | 4000 | < 20.6 |
| 140-062K-10GNE/840 | ø 633 × 125 | 71.6 | 7100 | 4000 | < 20.9 |
| 140-072K-12GEE/840 | ø 924 × 125 | 125.6 | 11800 | 4000 | < 20 |
| 140-082K-22GEE/840 | ø 1203 × 125 | 221.4 | 24290 | 4000 | < 20.2 |

These codes represent luminaires with chromaticity temperature 4000K and opal diffuser.

| | | |
|-------|---------------------------------|--|
| Notes | Colour Temperature | 3000 K warm white 4000 K cool white |
| | Optic system | Microprisma Opal diffuser |
| | Connection of the luminaires | ON/OFF DALI ON/OFF + 1h emergency ON/OFF + 3h emergency |
| | Ra | 80 |

Luminaires come complete with all necessary accessories.

Puri

Assembly

Light distribution

Energy class

A++, A+, A

Marks


| Code | Dimensions l/w/h (mm) | Power of the luminaire (W) | Luminous flux (lm) | Colour Temperature (K) | UGR |
|-----------------------|--------------------------|-------------------------------|-----------------------|------------------------------|--------|
| 141-043K-10GEE/840, W | ø 266 × 125 | 16.7 | 900 | 4000 | < 20.9 |
| 141-052K-10GHE/840, W | ø 384 × 125 | 17.1 | 1540 | 4000 | < 20.2 |
| 141-052K-10GIE/840, W | ø 464 × 125 | 32.8 | 3000 | 4000 | < 20.6 |
| 141-062K-10GNE/840, W | ø 664 × 125 | 71.6 | 7100 | 4000 | < 20.9 |
| 141-072K-12GEE/840, W | ø 964 × 125 | 125.6 | 11800 | 4000 | < 20 |
| 141-082K-22GEE/840, W | ø 1264 × 125 | 221.4 | 24290 | 4000 | < 20.2 |









AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

| | | |
|-------|------------------------------|---|
| Notes | Colour of the luminaires |  |
| | Colour Temperature | 3000 K warm white 4000 K cool white |
| | Optic system | Microprisma Opal diffuser |
| | Connection of the luminaires | ON/OFF DALI ON/OFF + 1h emergency ON/OFF + 3h emergency |
| | Ra | 80 |




Luminaires come complete with all necessary accessories.

Legend





Type of installation

| | |
|--|--|
|  Recessed lights |  Wall mounted lights |
|  Semi-recessed luminaire |  Suspended lights |
|  Surface lights |  Free-standing lights |
|  3 circuit track lights |  Table lamp lights |






Light distribution

| |
|--|
|  Direct luminaire |
|  Direct-indirect luminaire |
|  Indirect luminaire |

Light source

| | |
|---|--|
|  Tunable White adjusting the color temperature |  RealWhite true display of white color |
|  RealColour true display of colors Ra≥97 |  StrongColour highlight one color |

Marks

| |
|--|
|  Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable) |
|  Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable) |
|  Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation) |
|  European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it |
|  Luminaires are certified according to the European ENEC system |

 Recommended mounting hole size

IPxy IP code indicating the degree of protection of live parts

ERC Eurasian Conformity

09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

Optic system

Electrical connection

Colour









Optic system

| | |
|--|------------------------------------|
| C Clear cover | L Plain aluminium reflector |
| D Asymmetric reflector | M Matt parabolic louvre |
| E Polished parabolic louvre, high LOR | S SPOT - narrow angle |
| F FLOOD - wide angle | U MEDIUM - middle angle |
| I Microprismatic optical system | W Wide beam angle |
| K Opal diffuser | |

Electrical connection

| | |
|---|--|
| D DALI dimmable | P Sensor and electronic ballast |
| E Electronic ballast non-dimmable | T By switch dimmable (touch dimm) |
| M Electronic ballast non-dimmable with 1h emergency | TD DALI or by switch (touch dimm) dimmable |
| M3 Electronic ballast non-dimmable with 3h emergency | U Dimmable luminaire with dimmer on the luminaire |

Colour

| | | |
|--|--|--|
| W  White | B  Black | S  Silver |
| 1021  RAL 1021 | 3000  RAL 3000 | 6021  RAL 6021 |
| 7006  RAL 7006 | 7045  RAL 7045 | |