




Type of installation	Suspended
Light distribution	Direct, Direct-indirect
Colour of the luminaires	Black, Silver, White
Colour Temperature	3000 K warm white, 4000 K cool white
Material	Aluminium
Light source	LED MODUL
MacAdam Light source	3
Connection of the luminaires	ON/OFF DALI
Lifetime	L80/B20 50 000 hours
Warranty	60 months

Family

Rotao

Luminaire family variants Rotao



Rotao

Assembly

Light distribution

Energy class


A++, A+, A

Marks


Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
127-560K-10GEE/840, W	ø 600 × 87	23.7	2620	4000	-
127-561K-10GEE/840, W	ø 600 × 87	31	3400	4000	-
127-560K-10GGE/840, W	ø 600 × 87	35.1	3730	4000	-
127-561K-10GGE/840, W	ø 600 × 87	51.5	5090	4000	-
127-580K-10GEE/840, W	ø 850 × 87	49.5	5210	4000	-
127-581K-10GEE/840, W	ø 850 × 87	59.3	6190	4000	-
127-580K-10GGE/840, W	ø 850 × 87	66.2	6950	4000	-
127-581K-10GGE/840, W	ø 850 × 87	71	7480	4000	-
127-5B0K-10GEE/840, W	ø 1200 × 87	60.5	6290	4000	-
127-5B1K-10GEE/840, W	ø 1200 × 87	75.4	7770	4000	-
127-5B0K-10GGE/840, W	ø 1200 × 87	83	8630	4000	-
127-5B1K-10GGE/840, W	ø 1200 × 87	100.7	10370	4000	-
127-5C0K-10GEE/840, W	ø 1500 × 87	75.7	7870	4000	-
127-5C1K-10GEE/840, W	ø 1500 × 87	94.3	9710	4000	-
127-5C0K-10GGE/840, W	ø 1500 × 87	103.8	10790	4000	-
127-5C1K-10GGE/840, W	ø 1500 × 87	125.8	12960	4000	-

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

Notes

Colour of the
luminaires 

Colour Temperature 3000 K warm white
4000 K cool white

Optic system Microprisma
Opal diffuser









Connection of the
luminaires ON/OFF
DALI

Ra 80




Luminaires come complete with all necessary accessories.

Legend





Type of installation

 Recessed lights	 Wall mounted lights
 Semi-recessed luminaire	 Suspended lights
 Surface lights	 Free-standing lights
 3 circuit track lights	 Table lamp lights






Light distribution

 Direct luminaire
 Direct-indirect luminaire
 Indirect luminaire

Light source

 Tunable White adjusting the color temperature	 RealWhite true display of white color
 RealColour true display of colors Ra≥97	 StrongColour highlight one color

Marks

 Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
 Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
 Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
 European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
 Luminaires are certified according to the European ENEC system

 Recommended mounting hole size

IPxy IP code indicating the degree of protection of live parts

EARC Eurasian Conformity

09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

09-501I-20GGE/840, W

Optic system

Electrical connection

Colour









Optic system

C Clear cover	L Plain aluminium reflector
D Asymmetric reflector	M Matt parabolic louvre
E Polished parabolic louvre, high LOR	S SPOT - narrow angle
F FLOOD - wide angle	U MEDIUM - middle angle
I Microprismatic optical system	W Wide beam angle
K Opal diffuser	

Electrical connection

D DALI dimmable	P Sensor and electronic ballast
E Electronic ballast non-dimmable	T By switch dimmable (touch dimm)
M Electronic ballast non-dimmable with 1h emergency	TD DALI or by switch (touch dimm) dimmable
M3 Electronic ballast non-dimmable with 3h emergency	U Dimmable luminaire with dimmer on the luminaire

Colour

W  White	B  Black	S  Silver
1021  RAL 1021	3000  RAL 3000	6021  RAL 6021
7006  RAL 7006	7045  RAL 7045	